

AD-A053 191


UNIVERSITY OF STRATHCLYDE GLASGOW (SCOTLAND) CENTRE --ETC F/6 13/13  
ANALYSIS OF STRAIN HISTORIES IN STRUCTURES.(U)  
FEB 76 C A WALKER, J MCKELVIE, E R NORTH AFOSR-73-2566A  
EOARD-TR-76-001 NL

UNCLASSIFIED

| OF |  
AD  
A053191



END  
DATE  
FILMED  
6-78  
DDC



AD A053191

AD NO. \_\_\_\_\_  
DDC FILE COPY

Grant Number : AFOSR 73 - 2566A. **EOARD-TR-76-001**

Analysis of Strain Histories in Structures:

C.A. Walker:  
J. McKelvie:  
E.R. North:  
J.J.P. Sivewright:  
Centre for Industrial Innovation,  
Strathclyde University,  
Glasgow, Scotland.

(2)

B.S.

Feb 23 1976.

Final Report, June 01 1974 - May 31 1975.

Approved for public release;  
distribution unlimited.

Prepared for:

Wright - Patterson Air Force Base: Flight Dynamics Laboratory.

and

European Office of Aerospace Research and Development  
London, England.

DDC  
RECEIVED  
APR 26 1978  
B

## Analysis of Strain Histories in Structures

### Final Report

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL and/or SPECIAL
A	

#### Introduction:

The programme reviewed in this report was aimed at fulfilling a need perceived throughout the engineering industry, with particular reference for the aircraft designer; namely a technique for reliably measuring the deformations in structures under load. Such a system, now known as Optecord (an acronymic contraction of Optical Strain Recording) has been developed and field tested.

#### Scientific Basis:

Optecord is a moire' system, and as such depends upon a reference grid being attached to the specimen. . The grid follows the specimen deformation, and by comparison of the deformed grid with a master grid, the magnitude of strain over a whole area can be seen as a set of contour lines. The advances made during this programme consist of the development of a superior form of specimen grid which can reliably be used in almost any weather conditions, and of a replication method for acquiring the deformed grid data for comparison with the master. This comparison is carried out in an interferometer which multiplies the sensitivity obtained from the basic grid by a factor ranging between 15 and 50. By this means, an adequately sensitive measurement of engineering strain is possible. The system has already been described in detail in a previous Scientific Report (January, 1975).

#### Applications:

The system has been used successfully on road bridge, aircraft and oil-rig type structures, and for materials investigations, fatigue and fracture studies.

Future Developments:

A high temperature grid system is being developed which will take the operating temperature of the grids up to 1000°C, when monitoring of steam and gas turbine components will be possible. In addition a readout head for instant site readout of strain is under consideration.

Publications:

- 1) Interim Scientific Report AFOSR-73. dated Jan. 1975.
- 2) SESA Annual Conference, Chicago, May 1975. (submitted for publication in Experimental Mechanics).
- 3) British Society For Non-Destructive Testing, Annual Conference, Sept. 15, 1975, Cardiff.
- 4) Chartered Mechanical Engineer (to be published).
- 5) Strain (to be published).
- 6) British Journal of Non-Destructive Testing (to be published).

Communication with Wright-Patterson Air Force Base, Flight Dynamics Laboratory

Following the submission of the Final Scientific Report in January 1975, the Principal Investigator Dr. C.A. Walker, and Dr. J. McKelvie, paid a visit to the Photomechanics facility of the Flight Dynamics Lab at Wright-Patterson Air Force Base. A full discussion of the Optecord system took place, with mutual indication of areas of potential application.

During the same trip, a Seminar on Optecord was given at the Naval Research Lab, Ocean Technology Div, in Washington D.C.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER <b>EOARD-TR-76-001</b>	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) <b>Analysis of Strain Histories in Structures.</b>		5. TYPE OF REPORT & PERIOD COVERED <b>Final Rept.</b>	
7. AUTHOR(s) <b>C.A. Walkers J. McKelvie</b>		8. CONTRACT OR GRANT NUMBER(s) <b>AFOSR-73-2566A</b>	
9. PERFORMING ORGANIZATION NAME AND ADDRESS <b>University of Strathclyde, Centre for Industrial Innovation, Glasgow, Scotland.</b>		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS <b>61102F 9767-99-40</b>	
11. CONTROLLING OFFICE NAME AND ADDRESS <b>EOARD (BOX 14) FPO N.Y. 09510</b>		12. REPORT DATE <b>Feb. 23, 1976</b>	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) <b>EOARD (BOX 14) FPO N.Y. 09510</b>		13. NUMBER OF PAGES <b>14</b>	
		15. SECURITY CLASS. (of this report) <b>UNCLAS</b>	
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE			
16. DISTRIBUTION STATEMENT (of this Report) <b>Approved for public release; distribution unlimited.</b> <b>PE 61102F</b> <b>WU AFEDL 97679940</b>			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) <b>Multiplied Moire' Fringe. Relief Grating. Replication.</b>			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <b>→ A method for measuring strain contours on structures has been developed and tested. Based upon a multiplied moire' fringe technique, it uses a relief grating on the specimen and a replication technique to acquire the deformed grid data for subsequent analysis in a fringe-multiplying interferometer.</b>			